




## Fleet Specifications:

[PRINT THIS FORM](#)[SEND VIA EMAIL](#)

### **RIGID GENERAL TRAFFIC VEHICLES**

Drop sides available if required  
PLATFORM LENGTH: to 7.9m (26")  
CARRYING CAPACITY: 1,000 kilos (1 ton)  
to 14,000 kilos (14 tons)



### **SELF LOADING CRANE VEHICLES (FRONT MOUNTED)**

Drop sides available if required  
PLATFORM LENGTH: to 7.3m (24")  
CARRYING CAPACITY: 9,000 kilos (9 tons)  
CRANE CAPACITY: 3, 4, 5 tons maximum lift



### **SELF LOADING CRANE VEHICLES (REAR MOUNTED)**

PLATFORM LENGTH: to 7.3m (24")  
CARRYING CAPACITY: 7,000 kilos (7 tons)  
CRANE CAPACITY: 6 tons maximum lift



### **ARTICULATED FLAT AND EXTENDABLE LONG-LOAD TRAILERS**

Air suspension available on 40' trailers if required  
PLATFORM LENGTH: 10.1m (33'), 12.2m (40'), 13.7m (45')  
and extendables to 19.2m (63')  
CARRYING CAPACITY: 23,500 kilos (23 tons)



### **ARTICULATED REFRIGERATED TRAILERS**

Air suspension standard and with 24 pallet capacity  
BOX LENGTH: 12.2m (40')  
CARRYING CAPACITY: to 20,500 kilos (20.2 tons)



### **ARTICULATED TILT TRAILERS**

Air suspension standard  
TILT LENGTH: 12.2m (40')  
CARRYING CAPACITY: to 24,000 kilos (23.6 tons)



### **ARTICULATED LARGE CAPACITY SUPER CUBE TILT TRAILERS**

Air suspension standard and rear loading ramps available if required  
CUBIC CAPACITY: 82m<sup>3</sup> (2.895ft<sup>3</sup>)  
CARRYING CAPACITY: to 23,000 kilos (22.6 tons)



### **MACHINERY AND FORK LIFT TRUCK LOW LOADER**

Power winch facility and extra load-carrying well between trailer wheels  
MAIN WELL LENGTH: 6.2m (20.5')  
CARRYING CAPACITY: to 14,000 kilos (14 tons)



### **SEMI LOW LOADERS (NORMAL AND EXTENDABLE)**

PLATFORM LENGTHS: 7.6m (25'), 9.1m (30'), 12.2m (40')  
and extendables to 12.8m (42')  
CARRYING CAPACITY: to 25,000 kilos (25 tons)



### **LOW LOADERS**

Hydraulic detachable trailer neck with beaver tail low back bridge  
WELL LENGTH: from 6.1m (20') to 7.3m (24')  
CARRYING CAPACITY: to 50,000 kilos (50 tons)



### **HEAVY HAULAGE LOW LOADERS**

Hydraulic detachable trailer neck with beaver tail low back bridge  
WELL LENGTH: from 6.1m (20') to 7.3m (24')  
CARRYING CAPACITY: to 50,000 kilos (50 tons)